

A1
Concl.

with 48 columns on each deck. At any instant of time, for the exemplary antenna illustrated, only one third of the columns, a 120-degree sector, are excited to form a beam.

IN THE CLAIMS

Cancel Claims 1 and 6 without prejudice or disclaimer of the subject matter therein.

A2

2. (Amended) The antenna of Claim 20, wherein the ground surface structure is a magnetic conductor surface at an RF frequency band of interest, said ground plane structure functioning as a D.C. short and as a mirror which reflects an RF field in said frequency band with virtually no phase reversal.

3. (Amended) The antenna of Claim 20, wherein the protrusions form a very thin layer of a densely packed two-dimensional (2-D) periodic structure on top of a conducting surface, the periodic structure shielding the conducting surface underneath from inducing an image current to cancel the propagating E-field.

4. (Amended) The antenna of Claim 20, wherein the array of metal protrusions are formed as metal plates connected to the metal sheets by vertical posts.

A3

7. (Amended) The antenna of Claim 20 wherein the array further includes a true-time-delay corporate feed network connected to the radiating elements, wherein time delay differences in contributions by the individual radiating elements to a composite array signal due to the separation of the elements along the axis are equalized by the true-time delay corporate feed network.

A4

9. (Amended) The array of Claim 20 wherein each flared notch radiating element includes a pair of flared dipole wings.

A5
Cont.

13. (Amended) The antenna of Claim 12, wherein the beam-forming network includes a true-time-delay network, wherein time delay differences in